

# Venari GPS

## PRODUCT SHEET



**Part Number**

NWT-GPS-USB-OAS-02

**Product Description**

Industrial Outdoor IP67 Rated GPS, 2m Stainless Steel Armored USB, USB-A Male IP67 Watertight Assembly, Rigid ASA Plastic Housing, 72 Channel All-In-View Tracking, u-blox M8 Chipset, WAAS / EGNOS Support

**Product Overview**

Industrial Armored Outdoor GPS Receiver that features a highly sensitive, low power consumption chipset in an ultra compact outdoor form factor. Powered by a u-blox M8 Chipset, and will provide you with superior performance in urban canyons, and in dense foliage. CGEE-start time of less than 15 seconds under most conditions without any network assistance.

AWG	Stranding	Material	No of Pairs
28	7 x .127	TC - Tinned Copper	1
<b>Conductor Count</b>		4	
<b>Total Number of Pairs</b>		2	
<b>Conductor Size</b>		28AWG 1 Twisted Pr, 24 AWG 2C 7x.2 Stranded TC	
<b>Insulation Material</b>		PO - Polyolefin	
<b>Bonded-Pair</b>		No	

**OUTER SHIELD MATERIAL**

Type	Material	Coverage (%)	Drainwire Material	Drainwire AWG	Drainwire Construction (n x D)
Tape	Aluminum/ Mylar	100	Tinned Copper	28	7 x .127

**INNER JACKET MATERIAL**

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord	Separator Material
Industrial Grade PVC - Polyvinyl Chloride	0.45mm	0.8mm	No	Polyester

**ENVIRONMENT**

<b>Input Power Range</b>	4.5V-6.5V DC
<b>Current. Draw</b>	60mA typical, 100mA max
<b>USB Compliance</b>	Universal Serial Bus 2.0
<b>Frequency</b>	72-channel u-blox M8 engine GPS/QZSS L1 C/A, GLONASS L10F BeiDou B1, Galileo E1B/C SBAS L1 C/A: WAAS, EGNOS, MSAS, GAGAN
<b>C/A Code</b>	1.023 Mhz chip rate
<b>Sensitivity</b>	-167dBm Tracking & Nav, -160dBm Reacquisition -148dBm cold start
<b>Accuracy</b>	2.0M CEP
<b>Aquisition</b>	8sec avg hot start, 26sec cold start, 1sec hot start
<b>Connector type</b>	USB-A Male IP67 Watertight Assembly
<b>UL Voltage Rating (Cable)</b>	30V RMS
<b>Altitude Limit</b>	18,000M
<b>Velocity Limit</b>	515M/sec
<b>Acceleration Limit</b>	Less than 4g

# Venari GPS

## PRODUCT SHEET



### Part Number

NWT-GPS-USB-OAS-02

### Product Description

Industrial Outdoor IP67 Rated GPS, 2m Stainless Steel Armored USB, USB-A Male IP67 Watertight Assembly, Rigid ASA Plastic Housing, 72 Channel All-In-View Tracking, u-blox M8 Chipset, WAAS / EGNOS Support

### Product Overview

Industrial Armored Outdoor GPS Receiver that features a highly sensitive, low power consumption chipset in an ultra compact outdoor form factor. Powered by a u-blox M8 Chipset, and will provide you with superior performance in urban canyons, and in dense foliage. CGEE-start time of less than 15 seconds under most conditions without any network assistance.

### TEMPERATURE RANGE

<b>Installation Temp Range</b>	-40°C To +85°C
<b>UL Temp Rating</b>	85°C
<b>Operating Temp Range</b>	-40°C To +85°C

### MECHANICAL CHARACTERISTICS

<b>Dimension</b>	88mm X 79mm X 35mm
<b>Weight</b>	0.35kg
<b>Mounting Pipe Diameter</b>	25mm - 64mm

### MECHANICAL CHARACTERISTICS (OUTER CABLE ARMOR)

<b>Outside Diameter</b>	88mm X 79mm X 35mm
<b>USB Cable Length</b>	2M
<b>Jacket Material</b>	Black PVC
<b>Armor Material</b>	304 Stainless Steel

### STANDARDS

<b>GPS Standards</b>	NMEA 0183, WAAS, EGNOS, MSAS, QZSS, GAGAN, IMES
<b>RoHS Compliant</b>	Yes
<b>UL Type</b>	CM
<b>CSA Standards</b>	FT4
<b>Derating</b>	Operating temperatures are subject to de-rating. Cable passes -40°C Cold Bend per UL 1581

### SUITABILITY

<b>Indoor</b>	No
<b>Oil Resistance</b>	Yes
<b>Outdoor/Sunlight Exposure (UV)</b>	Yes
<b>Plenum</b>	No
<b>Direct Burial</b>	No

© 2024 Northwest Towers, LLC All Rights Reserved.

Although Northwest Towers makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Northwest Towers provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Northwest Towers be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Northwest Towers has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.